

SILIZED fuse links

Operational class gR

| | | | NEOZED design | | DIAZED design | | |
|-------|---------------------------|------------------|---|---|--|---|---|
| | | | Size D01 | Size D02 | Size DII | Size DIII | Size DIV |
| | | |  |  |  |  |  |
| I_n | Operating value I^2t | Power loss P_v | U_n AC/DC 400/250 V | U_n AC/DC 400/250 V | U_n AC/DC 500/500 V | U_n AC/DC 500/500 V | U_n AC/DC 500/500 V |
| 10 A | 73 A ² s | 6.9 W | 5SE1310 | – | – | – | – |
| 16 A | 60 A ² s | 12.1 W | – | – | 5SD420 | – | – |
| | 120 A ² s | 6.2 W | 5SE1316 | – | – | – | – |
| 20 A | 139 A ² s | 12.3 W | – | – | 5SD430 | – | – |
| | 190 A ² s | 8.1 W | – | 5SE1320 | – | – | – |
| 25 A | 205 A ² s | 12.5 W | – | – | 5SD440 | – | – |
| | 215 A ² s | 8.2 W | – | 5SE1325 | – | – | – |
| 30 A | 310 A ² s | 13.5 W | – | – | 5SD480 | – | – |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |

7

This job requires more memory than is available in this printer.

Try one or more of the following, and then print again:

For the output format, choose Optimize For Portability.

In the Device Settings page, make sure the Available PostScript Memory is accurate.

Reduce the number of fonts in the document.

Print the document in parts.