

I-system, Schuko+ 2USB Chargers Titan White



| Model  |                      |
|--|----------------------|
| product brand name   | DELTA                |
| product designation  | SCHUKO socket outlet |
| design of the product  | others               |
| cover version  | central plate        |
| design of the special power supply unit                            | Other                |
| design of the socket / according to VDE 0620 for severe conditions | No                   |
| design of the phase tap  | No                   |
| General technical data   |                      |
| marking / of socket outlet   | without imprint      |
| mounting type  | fixing with screw    |
| surface processing   | Untreated            |
| material   | thermoplastic        |
| Supply voltage   |                      |
| operating voltage / rated value                                    | 250 V                |
| Protection class   |                      |
| protection class IP  | IP20                 |

| Main circuit                        |               |
|-------------------------------------|---------------|
| operating current                   |               |
| • rated value                       | 16 A          |
| Appearance                          |               |
| color                               | Titanium      |
| Product details                     |               |
| product component                   |               |
| • ejection equipment                | No            |
| • labeling field                    | No            |
| • increased touch protection        | Yes           |
| • fault current protection          | No            |
| • miniature fuse                    | No            |
| • integrated / functional lighting  | No            |
| • integrated / light source         | No            |
| • integrated / orientation lighting | No            |
| • hinged lid                        | No            |
| product feature                     |               |
| • lockable                          | No            |
| • halogen-free                      | Yes           |
| • transparent                       | No            |
| Product function                    |               |
| product function                    |               |
| • socket selectable                 | No            |
| • overvoltage protection            | No            |
| Number                              |               |
| number of units                     | 1             |
| number of sockets / switchable      | 0             |
| Connections                         |               |
| arrangement of contacts / diagonal  | No            |
| type of electrical connection       | plug terminal |
| Mechanical Design                   |               |
| height                              | 70.5 mm       |
| width                               | 70.5 mm       |
| depth                               | 53 mm         |
| mounting type                       | flush mounted |
| material / of the enclosure         | plastic       |
| Certificates                        |               |



EG-Konf.

Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=5UB1970-0TW01>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/5UB1970-0TW01>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mfb=5UB1970-0TW01](http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=5UB1970-0TW01)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>