SIEMENS

Product data sheet 8WD4200-1AE



STEADY-LIGHT ELEMENTS, CLEAR AC/DC 24V...230V

General technical details:			
product brand name		SIRIUS	
product designation		signaling columns element, optical	
Product component / fluorescent materials		No	
Design of the optical signal		continous light	
Type of voltage			
of the operating voltage		AC/DC	
Operating frequency			
• 1 / rated value	Hz	50	
• 2 / rated value	Hz	60	
Operating voltage			
• for DC / rated value	V	230 24	
• at 50 Hz / at AC / rated value	V	24 230	
• at 60 Hz / at AC / rated value	V	24 230	
Item designation			
 according to DIN 40719 extendable after IEC 204-2 / according to IEC 750 		Н	
according to DIN EN 61346-2		P	

Mechanical design:	
Color / of the optical signal element	clear

External diameter / of the signal column element mm 50 Lamp: Nature of fluorescent material filament lamp / LED **Ambient conditions: Ambient temperature** °C -20 ... +50 during operating **Protection class IP** IP54 Depth mm 50 Height 55 mm Width 50 mm

Certificates/approvals:

General Product Approval

EMC

Declaration of Conformity

Shipping Approval











Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/industrial-controls/catalogs

Industry Mall (Online ordering system)

http://www.siemens.com/industrial-controls/mall

Cax online generator:


http://www.siemens.com/cax


Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

http://support.automation.siemens.com/WW/view/en/8WD4200-1AE/all

 $Image\ database\ (product\ images,\ 2D\ dimension\ drawings,\ 3D\ models,\ device\ circuit\ diagrams,\ ...)$

 $\underline{\text{http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WD4200-1AE}$







\W9.4444; \W6.8611; 8WD

last change:

Sep 2, 2013